

1-1-1979

# Precision Requirement in Measuring Aerosol Load for Remote Sensing Applications

R. K. Kiang

S. G. Ungar

E. S. Bryant

Follow this and additional works at: [http://docs.lib.purdue.edu/lars\\_symp](http://docs.lib.purdue.edu/lars_symp)

---

Kiang, R. K.; Ungar, S. G.; and Bryant, E. S., "Precision Requirement in Measuring Aerosol Load for Remote Sensing Applications" (1979). *LARS Symposia*. Paper 247.  
[http://docs.lib.purdue.edu/lars\\_symp/247](http://docs.lib.purdue.edu/lars_symp/247)

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact [epubs@purdue.edu](mailto:epubs@purdue.edu) for additional information.

Reprinted from

**Symposium on**

**Machine Processing of**

**Remotely Sensed Data**

**June 27 - 29, 1979**

The Laboratory for Applications of  
Remote Sensing

Purdue University  
West Lafayette  
Indiana 47907 USA

IEEE Catalog No.  
79CH1430-8 MPRSD

Copyright © 1979 IEEE  
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to [pubs-permissions@ieee.org](mailto:pubs-permissions@ieee.org).

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

## PRECISION REQUIREMENT IN MEASURING AEROSOL LOAD FOR REMOTE SENSING APPLICATIONS

R. K. KIANG AND S. G. UNGAR

NASA Goddard Institute for Space Studies

E. S. BRYANT

Dartmouth College

The effects of atmospheric aerosol on remote sensing application have been widely studied, and the possibility of actually measuring the aerosol optical thickness either by ground-based devices or by sensors on board satellites has begun to attract attention. It is thus essential to estimate the required precision in such measurement for improving classification accuracy.

Forestry data from intensively studied area of New Hampshire and Maine\* have been classified with several simulated aerosol distributions. It is assumed that the actual aerosol optical thickness was 0.15 over the area classified. Radiance is transformed according to parameters obtained from a doubling model to simulate aerosol effects. Atmospheres with aerosol distributions of average optical thickness 0.05, 0.25, 0.35 and 0.45 were simulated for both homogeneous and inhomogeneous conditions.

Preliminary results show that difference of 0.1 in the optical thickness between training and application sites leads to a decrease of 5 to 30% in the relative classification accuracy for various types of forest. It is concluded that measurements of aerosol optical thickness must be made with a precision of 0.01.

---

\*Dodge and Bryant, J. of Forestry, Vol. 74, No. 8, 1976.